



## Paintworks Specification PS 2081.06

---

**Product** Eco Weather Proof Exterior Low Sheen

---

**Substrate** Exterior – New & Unpainted Masonry, Brick, Cement, Render & Fibre Cement

---

**Category** Premium – Water Based

---

### Product Description

Eco Weather Proof Exterior Low Sheen is a zero VOC, acrylic paint that produces a premium quality low sheen finish. Can be tinted to all colours on Ecolour charts as well as most other colour charts. Available in four bases: white, light tone, mid tone and strong.

---

### Recommended Uses

Suitable for exterior walls and ceilings. A low sheen finish that provides exceptional coverage.

---

### Surface Preparation

Ensure surfaces to be painted are clean and free of dust, dirt, and mould. Fill any cracks or holes with a suitable filler.

---

Application Details	Data Sheet	Coverage m <sup>2</sup> /L	Film Thickness		Dry Times	
			Wet	Dry	Touch	Recoat
First Coat:	Primer Undercoat (DS1.01)	8-10m <sup>2</sup> /L	75	55	30 mins	2 hours
Second Coat:	Eco Weather Proof Exterior Low Sheen (DS8.01)	16m <sup>2</sup> /L	75	55	30 mins	2 hours
Third Coat:	Eco Weather Proof Exterior Low Sheen (DS8.01)	16m <sup>2</sup> /L	75	55	30 mins	2 hours

\*An additional coat may be required if using or painting over deeper colours.

---

### Care and Maintenance

This product will provide a scrubbable surface that can be wiped clean with a damp cloth. Surface scratches can be repaired by cutting back and re-coating.

---

### Caution

With zero Volatile Organic Compounds (VOCs) outgassing, it is NOT necessary to provide adequate ventilation when applying for health reasons. However, in a low airflow environment, it is advisable to provide airflow to assist with drying. Application should not be carried out if the air temperature or substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.

---

### Customer Support

For additional information, including technical advice, assistance with specifying, brush out samples or any other related topic please contact Ecolour on 1300 326 568 or [info@ecolour.com.au](mailto:info@ecolour.com.au).

---