



MicroClear EXTERIOR



- Description:** MICROCLEAR EXTERIOR IS A WATERBORNE OIL MODIFIED URETHANE ALKYD, DRYING TO A MEDIUM GLOSS FINISH WITH VERY LITTLE YELLOWING.
- MICROCLEAR EXTERIOR IS A SINGLE PACK HARDWEARING WATER CLEAR, FAST DRYING COATING WITH A VERY SMOOTH FLOW AND SELF LEVELLING FINISH. IT IS TINTABLE, NON TOXIC, LOW ODOUR AND V.O.C. COMPLIANT.
- .
- Suitable** Exterior surfaces doors & windows, feature walls exterior furniture.
Micro Clear Exterior is best used in semi shaded areas.
- Application:** Exterior timber surfaces must be fresh and clean. Apply by brush, short nap 8-9mm roller or spray. MicroClear Exterior causes very little grain raising on most wood, MicroClear Exterior is fast drying; multiple coats per day are possible. Avoid using over 31 degrees, one hour drying time between coats is advised. Minimum of 3 coats are required. Sanding between coats is not usually required; however a light de-nibbing after first coat may be beneficial. After curing has taken place, surfaces may be cleaned with mild detergent and water. **For best results** apply Micro clear over **Nano Tinted Primer**, This is available in clear or Transparent colours.
- Coverage:** 10-16 square metres per litre. First coat can use a little more.
- Spraying:** Airless spray 313-315 tip, H.V.L.P. or air spray.
MicroClear Exterior can be reduced by 5% with water.
- Drying Time:** MicroClear Exterior is fast drying, touch dry in 30 minutes at 25°. Full hardness and cure may take 30 days. Care should be taken with new surfaces.
- Tinting:** MicroClear Exterior can be tinted with machine tints or Wood tone transparent tints, or as an overcoat to Quantum Nano Tinted Primer.
- Recoating** When recoating a fine sand back to a peach like finish is recommended. If coating over multiple days cross linking may occur so using a fine sanding paper in between coats is advisable.
- Clean up:** Wash brushes and tools in soap and water.
- Disclaimer:** Recycled timber should always be tested prior to application on an off-cut or small patch out of sight. This test needs to be done for adhesion and over-coating.
- Environment:** Quantum Timber Finishes do not use mineral spirit products in manufacturing; hence all Quantum products are low in VOCs. **VOC <135g/litre**

The entire range is free of hazardous air pollutants (HAPS).

Ph: 03 9776 8831

Fax: 03 9782 4417

Freecall: 1800 053 018

quantum@qtf.com.au