

## Paintworks Specification PS 1041.10

---

**Product**                      **Wet Area Satin**

---

**Substrate**                    Interior – New & Unpainted Bare Iron & Steel

---

**Category**                    Premium – Water Based

---

### Product Description

Wet Area Satin is a zero VOC, acrylic paint that produces a premium quality satin finish. Can be tinted to all colours on Ecolour charts as well as most other colour charts. Available in four bases: white, light tone, mid tone and strong.

---

### Recommended Uses

Suitable for interior walls and ceilings in wet areas. A satin finish that provides exceptional coverage.

---

### Surface Preparation

Ensure surfaces to be painted are clean and free of dust, dirt, mould and contaminants. Fill any cracks or holes with a suitable filler.

---

Application Details	Data Sheet	Coverage m <sup>2</sup> /L	Film Thickness		Dry Times	
			Wet	Dry	Touch	Recoat
First Coat:	Primer Undercoat (DS1.01)	8-10m <sup>2</sup> /L	75	55	30 mins	2 hours
Second Coat:	Wet Area Satin (DS4.01)	16m <sup>2</sup> /L	75	55	30 mins	2 hours
Third Coat:	Wet Area Satin (DS4.01)	16m <sup>2</sup> /L	75	55	30 mins	2 hours

\*An additional coat may be required if using or painting over deeper colours.

---

### Care and Maintenance

This product will provide a scrubbable surface that can be wiped clean with a damp cloth. Surface scratches can be repaired by cutting back and re-coating.

---

### Ventilation

With zero Volatile Organic Compounds (VOCs) outgassing, it is NOT necessary to provide adequate ventilation when applying for health reasons. However, in a low airflow environment, it is advisable to provide airflow to assist with drying. Application should not be carried out if the air temperature or substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.

---

### Customer Support

For additional information, including technical advice, assistance with specifying, brush out samples or any other related topic please contact Ecolour on 1300 326 568 or info@ecolour.com.au.

---