

Paintworks Specification PS 1051.06

Product Polyclear

Substrate Interior – New & Unpainted Hard Set Fibrous Plaster & Plaster Glass

Category Premium – Water Based

Product Description

Polyclear is a unique and tough hard surface sealer that provides maximum protection. It provides a clear, hard finish for timber and concrete. It can be tinted to many opaque colours.

Recommended Uses

Suitable for interior timber, including; doors, trim work, furniture, window frames and paneling. Suitable for timber and concrete internal floors. Not suitable for surfaces where water can form puddles as it may appear milky until water dries.

Surface Preparation

Ensure surfaces to be painted are clean and free of dust, dirt, mould, grease, contaminants and any flaking or blistering finishes. Fill any cracks or holes with a suitable filler.

Application Details	Data Sheet	Coverage m ² /L	Film Thickness		Dry Times	
			Wet	Dry	Touch	Recoat
First Coat:	Polyclear (DS5.01)	8-10m ² /L	90	55	30 mins	2 hours
Second Coat:	Polyclear (DS5.01)	16m ² /L	90	55	30 mins	2 hours
Third Coat:	Polyclear (DS5.01)	16m ² /L	90	55	30 mins	2 hours

*3 coats are recommended for floors, 2 coats are recommended for all other surfaces

Care and Maintenance

Polyclear will provide a clear, scrubbable surface that can be wiped clean with a damp cloth. Surface scratches can be repaired by cutting back and re-coating.

Ventilation

With zero Volatile Organic Compounds (VOCs) outgassing, it is NOT necessary to provide adequate ventilation when applying for health reasons. However, in a low airflow environment, it is advisable to provide airflow to assist with drying. Application should not be carried out if the air temperature or substrate temperature is below 10°C or above 35°C. The temperature must not fall below 10°C during the drying process.

Customer Support

For additional information, including technical advice, assistance with specifying, brush out samples or any other related topic please contact Ecolour on 1300 326 568 or info@ecolour.com.au.
